



RELEASED

07.08.29

D2499 MOUNT

NOTES:

- 1) MATERIAL: 6061-T6 (OR 6061-T651/T6510/T6511/T62) BAR
PER AMS-QQ-A-225/8 (OR AMS 4117/4128/4115/4116)
PER AMS-QQ-A-200/8 (OR AMS 4160)
(REF. DART SPEC. M6061T6B)
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI005 4.1
POWDER COAT WHITE (4.3.5.1) PER DART QSI005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D2499" USING FINE
POINT PERMANENT INK MARKER
- 7) WEIGHT: 0.65 lbs

C	- ADDED MASKING DETAIL - DUE TO TIGHT FIT WHEN INSTALLED ON BASKET - ADD MASKING STEP TO ESTIMATE	DC	07.07.25
B	CHANGE HOLE DIA TO .386	KH	95.12.06
A	NEW ISSUE	BW	95.11.09
REV.	DESCRIPTION	BY	DATE
DESIGN	B WILLIAMS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	SK	DRAWING NO.	REV. C
CHECKED	SK	D2499	SHEET 1 OF 1
MFG. APPR.	SK	TITLE	SCALE
APPROVED	SK	MOUNT	1:2
DE APPR.	SK		
DATE	07.07.25	COPYRIGHT © 1995 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	